

IMPORTANT OWNER INSTALLATION AND MAINTENANCE INSTRUCTIONS

DO NOT THROW AWAY

(Des instructions en français sont incluses)

Product : *Tank tub and cover*

Models: TC1 and TC2

Capacity: Up to 1135 litres or 330 US gals

Usage: For secondary containment, weather protection and aesthetic improvement of domestic, obround, vertical heating oil tanks. For indoor (TC1) and outdoor (TC2) use.

CAUTION ! Be careful when unpacking. This package contains Instruction sheet and an installation kit. If Installation Instructions or pieces are missing, please advise our Customer Service Department at 450-378-2334; and mention the name and area of your Granby Steel Tanks Distributor.

INSTALLATION

- Follow the Installation Instructions included in this package;
- Use caulking for outdoor installation to seal the upper part of the back sides joint, to avoid conditions where heavy pouring water could fill the basin;
- Do not perforate the basin on any purpose; take care the steel plate stay under the tank legs when tank is installed.

MAINTENANCE

Periodically inspect tank and containment for proper operation, including:

- Leakage of tank by visual check to detect any oil in or around the basin;
- Visually check the vent pipe and cap are free of obstruction;
- Physical damage to the containment and cover system as described below, or other suspected damage :
 - Any cuts or holes in the plastic shell;
 - Any abnormal bending of the burner connection pipe;
 - Any loosening of the fill, vent and gauge fittings;
 - Any bending or leaning of the tank support;
 - Permanent deformations in the plastic shell;
 - Improper fit of the tank cover (Outdoor installation).

CAUTION ! If the above or other hazardous conditions are found, please contact immediately the installer :

- Or you can join Granby Steel Tanks at www.granbytanks.com or by phone customer service at 450-378-2334

WARNINGS !

- Install on a proper levelled base, concrete pad is recommended;
- Do not load or stand on top of the basin or the cover;
- For installation only by a licensed installer – Do not move or modify after installation;
- For outdoor use: The cover must be secured after each fill or inspection – Do not remove the cover.