

COMMERCIAL ABOVEGROUND STORAGE TANKS ULC-S602



BUILT TOUGH TO HANDLE ANY JOB

Tough and durable, our commercial aboveground storage tanks will meet your various requirements



GRANBYINDUSTRIES.COM

AUXILIARY TANKS

GENERAL SPECIFICATIONS

- » ASTM A1011 Steel
- » NPT female threaded openings
- » Capacity ranging from 50 to 500 Gallons
- » Double wall design
- » Each tank is manufactured, controlled, tested, and labeled in accordance with ULC-S602 standard for fuel oil and lubricating oil



Shown: 500 Gallons

ULC-S602 DOUBLE WALL TANK

- Capacities ranging from 50 to 500 gallons
- The double wall interstice is factory shipped under vacuum for constant monitoring of both walls' integrity
- Equipped with a vacuum gauge for visual monitoring of leaks in the interstitial space
- Optional vacuum loss switch
- Vacuum leak detection monitoring system can be replaced on site by a liquid leak detector (mechanical or electronic)
- Up to eight (8) openings on top
- Steel surface is phosphate washed and coated with Granby's white polyurethane paint



Shown: 250 Gallons

ULC-S602 DOUBLE WALL VERTICAL TANK

- Capacity ranges from 50 to 500 gallons
- Double wall construction (except for top cover)
- Two interstitial space monitoring designs available:
 - Vacuum (VCD models) with constant monitoring of both walls' integrity.
 - Factory shipped with a vacuum gauge for visual monitoring of leaks in the interstitial space
 - Optional vacuum switch
 - Secondary containment (VCC models) with constant visual monitoring of liquid in the interstitial space
 - Factory shipped with a visual mechanical float indicator
 - Optional electronic liquid detector for the interstitial space monitoring
- Strong base support with floor anchors
- Designed with up to 8 top openings

TANK CAPACITY AND DIMENSIONS

Granby Storage Tanks offers commercial aboveground tanks of different capacities for the storage of diesel, heating oils, or lubricating oils. Tank weight varies according to the chosen model and options. Refer to the table or to our website for further details.

ULC-S602 - DOUBLE WALL - INTEGRALLY CONTAINED WITH VACUUM MONITORING								
PART #	LITERS	GAL	DIA	LENGTH	TANK SUPPORT L= LEGS S= SKIDS	STEEL THICKNESS	POUNDS	KG
3002C222NCAA	227	50	23"	40"	L	2,5mm	199	90
3006C222NCAA	570	125	30,5"	49"	L	2,5mm	341	155
3014C222NCAA	1360	300	50,5"	72"	L	2,5mm	601	273
3023C242NCAA	2275	500	50,5"	72"	L	2,5mm	867	394

ULC-S602 - VERTICAL DOUBLE WALL INTEGRALLY CONTAINED								
CLOSED SECONDARY CONTAINMENT TANK, ULC-S602 LISTED								
PART #	LITERS	GAL	DIA	LENGTH	GAUGE	POUNDS	KG	
VCC22050NCAA	227	50	22,75"	42,75"	2,5mm	214	97	
VCC22100NCAA	454	100	30,75"	46"	2,5mm	314	143	
VCC22150NCAA	680	150	30,75"	66"	2,5mm	427	194	
VCC22200NCAA	910	200	38,5"	55"	2,5mm	488	222	
VCC22250NCAA	1135	250	38,5"	66"	2,5mm	562	255	
VCC22300NCAA	1360	300	38,5"	78"	2,5mm	643	292	
VCC22500NCAA	2275	500	50,5"	78"	2,5mm	904	411	

VACUUM MONITORED TANK, ULC-S602 LISTED								
PART #	LITERS	GAL	DIA	LENGTH	GAUGE	POUNDS	KG	
VCD22050NCAA	227	50	22,75"	42,75"	2,5mm	214	97	
VCD22100NCAA	454	100	30,75"	46"	2,5mm	314	143	
VCD22150NCAA	680	150	30,75"	66"	2,5mm	427	194	
VCD22200NCAA	910	200	38,5"	55"	2,5mm	488	222	
VCD22250NCAA	1135	250	38,5"	66"	2,5mm	562	255	
VCD22300NCAA	1360	300	38,5"	78"	2,5mm	643	292	
VCD22500NCAA	2275	500	50,5"	78"	2,5mm	904	411	



Contact your representative for more information on the different additional accessories available.



For more information, please contact the head office
 98, rue des Industries
 Cowansville (Quebec) J2K 0A1 Canada
 ✉ sales@granbyindustries.com
 🌐 granbyindustries.com