



# MAC / MACF COMBI GAS BOILER

## PRODUCT SPECIFICATIONS

MODELS			INPUT MBH <sup>(1)</sup>				DHW	AHRI CERTIFIED RATINGS		
Type	Wall Mounted	Floor Standing	CH Mode MAX	CH Mode MIN	DHW Mode MAX	DHW Mode MIN	Flow Rate GPM <sup>(4)</sup>	Heating Capacity MBH <sup>(1)(2)</sup>	Net Water MBH <sup>(1)(3)</sup>	Efficiency AFUE <sup>(2)</sup>
COMBI	MAC-115	MACF-115	93.5	16.6	115.5	16.6	2.5	85.4	74	95%
	MAC-150	MACF-150	125	22.0	153	22.0	3.5	113	98	95%
	MAC-205	MACF-205	164	29.5	205	29.5	5.0	153	133	95%

(1) 1000 Btu/h (British Thermal Units Per Hour)

(2) Heating capacity and AFUE (Annual Fuel Utilization Efficiency) are based on DOE (Department of Energy) test procedures.

(3) Net AHRI Ratings based on piping and pickup allowance of 1.15. Consult manufacturer before selecting boiler for installations having unusual piping and pickup requirements, such as intermittent system operation, extensive piping systems, etc.

(4) DHW (Domestic Hot Water) Flow Rate based on 70°F (21°C) temperature rise.

DIMENSIONS	WALL MOUNTED	FLOOR STANDING
Height	30"	43 3/4" (Bottom of boiler to top of safety valve)
Width	17 3/4"	24 3/4" (Overall with manifold)
Depth	13 9/16" (115/150) 21 1/2" (205)	17 1/2" (115/150) 23 1/2" (205)

TAKE ADVANTAGE OF  
**REBATES**  
with **95% AFUE\***

\*Heating equipment efficiency is measured by the Annual Fuel Utilization Efficiency (AFUE) ratio. It measures how efficiently fuel is transformed into heat for your home. The higher the AFUE rating, the greater the efficiency and reduction in fuel consumption.



[www.granbyindustries.com](http://www.granbyindustries.com)

All specifications subject to change without notice.  
Rev. [12/14/22]



Floor Standing  
MACF

Wall Mounted  
MAC